



LAVORAZIONE E COMMERCIO LAMIERE ZINCATE - PREVERNICIATE E NERE

Tel. 0565 220774 (4 linee r.a.) - Fax 0565 220253

Internet: www.etruscaprofilati.it

E-mail: commerciale@etruscaprofilati.it

EP38			
Caratteristiche statiche			
Spessore	Peso Kg/m ²	Peso Kg/m	
		1000	1250
0.6	6.43	4.71	5.89
0.7	7.5	5.5	6.87
0.8	8.58	6.28	7.85

EP38													
Spessore	Carico massimo uniformemente distribuito in kN/m ²												
mm	1 campata												
	1	1.25	1.5	1.75	2	2.25	2.5	2.75	3	3.25	3.5	3.75	4
0.6	4.8	3.05	2.1	1.53	1.16	0.8 0.9	0.57 0.72	0.41 0.59	0.3 0.48	0.22 0.4	0.17 0.34	0.12 0.29	0.09 0.25
0.7	5.76	3.66	2.52	1.84	1.36 1.39	0.96 1.08	0.66 0.87	0.48 0.7	0.35 0.58	0.26 0.49	0.19 0.41	0.14 0.35	0.11 0.3
0.8	6.72	4.28	2.95	2.14	1.55 1.62	1.06 1.27	0.75 1.01	0.54 0.82	0.4 0.68	0.3 0.57	0.22 0.48	0.16 0.41	0.12 0.35

EP38													
Spessore	Carico massimo uniformemente distribuito in kN/m ²												
mm	2 campate												
	1	1.25	1.5	1.75	2	2.25	2.5	2.75	3	3.25	3.5	3.75	4
0.6	7.26	4.66	3.23	2.37	1.8	1.41	1.14	0.93	0.77 0.77	0.59 0.65	0.46 0.55	0.36 0.47	0.29 0.41
0.7	8.3	5.33	3.7	2.7	2.06	1.61	1.3	1.06	0.88	0.71 0.74	0.55 0.63	0.43 0.54	0.34 0.47
0.8	9.34	6	4.16	3.04	2.32	1.82	1.46	1.19	0.99	0.83	0.65 0.71	0.51 0.61	0.41 0.52

EP38													
Spessore	Carico massimo uniformemente distribuito in kN/m ²												
mm	N campate												
	1	1.25	1.5	1.75	2	2.25	2.5	2.75	3	3.25	3.5	3.75	4
0.6	7.53	4.8	3.32	2.42	1.84	1.44	1.07 1.16	0.79 0.95	0.59 0.79	0.45 0.66	0.35 0.56	0.27 0.48	0.21 0.42
0.7	9.04	5.76	3.98	2.91	2.21	1.73	1.28 1.39	0.94 1.14	0.71 0.95	0.54 0.8	0.42 0.68	0.33 0.58	0.26 0.5
0.8	10.55	6.72	4.65	3.39	2.58	2.02	1.51 1.62	1.11 1.33	0.84 1.1	0.64 0.93	0.49 0.79	0.39 0.68	0.3 0.59

I valori in Grassetto sono riferiti ad una freccia >1/200 L