

EP75

Caratteristiche statiche

Spessore	Peso Kg/m ²	Peso Kg/m
0.8	11.02	6.28
1.0	13.77	7.85
1.2	16.53	9.42



LAVORAZIONE E COMMERCIO LAMIERE ZINCATE - PREVERNICIATE E NERE

Tel. 0565 220774 (4 linee r.a.) - Fax 0565 220253
 Internet: www.etruscaprofilati.it
 E-mail: commerciale@etruscaprofilati.it

LAMIERA GRECATA EP75

EP75

Spessore	Carico massimo uniformemente distribuito in kN/m ²																			
mm	1 campata																			
	1.5	1.75	2	2.25	2.5	2.75	3	3.25	3.5	3.75	4	4.25	4.5	4.75	5	5.25	5.5	5.75	6	
0.8	17.35	12.71	9.7	7.37	5.34	3.98	3.03	2.36	1.86	1.49	1.2	0.98	0.8	0.66	0.55	0.46	0.38	0.32	0.26	
				7.64	6.17	5.08	4.25	3.6	3.09	1.67	2.34	2.05	1.8	1.62	1.45	1.31	1.18	1.07	0.97	
1.0	21.06	15.43	11.8	9.2	6.66	4.96	3.78	2.94	2.32	1.86	1.5	1.22	1	0.83	0.69	0.57	0.47	0.39	0.33	
				9.28	7.48	6.16	5.15	4.37	3.74	3.24	2.83	2.49	2.21	1.96	1.76	1.58	1.43	1.29	1.17	
1.2	26.02	19.07	14.5	11.02	7.98	5.94	4.53	3.52	2.78	2.22	1.8	1.46	1.2	0.99	0.82	0.68	0.57	0.47	0.39	
				11.46	9.25	7.61	6.37	5.4	4.63	4.	3.5	3.08	2.73	2.43	2.18	1.96	1.77	1.6	1.46	

EP75

Spessore	Carico massimo uniformemente distribuito in kN/m ²																			
mm	2 campate																			
	1.5	1.75	2	2.25	2.5	2.75	3	3.25	3.5	3.75	4	4.25	4.5	4.75	5	5.25	5.5	5.75	6	
0.8	9.61	7.08	5.41	4.26	3.44	2.83	2.36	1.99	1.7	1.47	1.28	1.12	0.99	0.87	0.78	0.69	0.62	0.56	0.5	
1.0	14.09	10.37	7.93	6.25	5.05	4.15	3.47	2.93	2.5	2.17	1.89	1.66	1.46	1.3	1.16	1.04	0.93	0.84	0.76	
1.2	17.34	12.76	9.76	7.7	6.21	5.11	4.27	3.61	3.1	2.67	2.33	2.04	1.8	1.6	1.43	1.28	1.15	1.03	0.94	

EP75

Spessore	Carico massimo uniformemente distribuito in kN/m ²																			
mm	N campate																			
	1.5	1.75	2	2.25	2.5	2.75	3	3.25	3.5	3.75	4	4.25	4.5	4.75	5	5.25	5.5	5.75	6	
0.8	11.12	8.2	6.29	4.96	4	3.3	2.76	2.33	2	1.73	1.5	1.32	1.16	1.03	0.92	0.82	0.71	0.66	0.56	
																		0.67	0.6	
1.0	16.3	12.02	9.22	7.27	5.88	4.84	4.05	3.43	2.94	2.54	2.22	1.95	1.72	1.53	1.37	1.22	1.04	0.89	0.76	
																	1.23	1.11	1	0.9
1.2	20.08	14.81	11.34	8.95	7.23	5.96	4.98	4.22	3.62	3.13	2.73	2.4	2.12	1.89	1.69	1.47	1.25	1.07	0.92	
																1.51	1.36	1.23	1.12	

I valori in grassetto sono riferiti ad una freccia >1/200 L