

EP55

Caratteristiche statiche

Spessore	Peso Kg/m ²	Peso Kg/m	
		1000	1250
0.8	10.47	6.28	7.85
1.0	13.08	7.85	9.81
1.2	15.7	9.42	11.78



Trusca Profilati s.r.l.
STEEL SERVICE CENTRE

EP55

Spessore

Carico massimo uniformemente distribuito in kN/m²

mm	1 campata																
	1.0	1.25	1.5	1.75	2.0	2.25	2.5	2.75	3	3.25	3.5	3.75	4	4.25	4.5	4.75	5
0.8	18.87	12.05	8.34	6.1	4.65	3.39 3.66	2.44 2.95	1.81 2.42	1.37 2.02	1.06 1.71	0.83 1.46	0.66 1.26	0.52 1.1	0.42 0.96	0.34 0.85	0.27 0.75	0.22 0.67
1.0	25.96	16.58	11.48	8.4	6.41	4.5 5.04	3.25 4.06	2.41 3.34	1.83 2.79	1.41 2.36	1.11 2.02	0.88 1.74	0.7 1.52	0.56 1.33	0.46 1.18	0.37 1.05	0.3 0.93
1.2	34.24	21.87	15.14	11.09	8.13 8.46	5.67 6.66	4.09 5.37	3.04 4.41	2.31 3.69	1.78 3.12	1.4 2.67	1.11 2.31	0.89 2.02	0.72 1.77	0.58 1.57	0.47 1.39	0.38 1.24

EP55

Spessore

Carico massimo uniformemente distribuito in kN/m²

mm	2 campata																
	1.0	1.25	1.5	1.75	2.0	2.25	2.5	2.75	3	3.25	3.5	3.75	4	4.25	4.5	4.75	5
0.8	19.49	12.57	8.75	6.43	4.91	3.87	3.12	2.57	2.14	1.81	1.55	1.34	1.17	1.03	0.91	0.80	0.68 0.72
1.0	27.34	17.68	12.33	9.07	6.94	5.47	4.41	3.63	3.04	2.57	2.2	1.91	1.66	1.46	1.29	1.09 1.15	0.91 1.03
1.2	34.07	22.06	15.39	11.33	8.67	6.84	5.52	4.54	3.8	3.22	2.76	2.39	2.08	1.83	1.62	1.37 1.44	1.15 1.29

EP55

Spessore

Carico massimo uniformemente distribuito in kN/m²

mm	N campate																
	1.0	1.25	1.5	1.75	2.0	2.25	2.5	2.75	3	3.25	3.5	3.75	4	4.25	4.5	4.75	5
0.8	22.5	14.56	10.15	7.47	5.71	4.5	3.64	2.99	2.5	2.12	1.7 1.82	1.36 1.57	1.1 1.37	0.9 1.21	0.75 1.07	0.62 0.95	0.52 0.85
1.0	31.5	20.44	14.29	10.52	8.06	6.36	5.14	4.24	3.54	2.85 3.01	2.26 2.58	1.81 2.23	1.47 1.95	1.21 1.72	1 1.52	0.83 1.35	0.69 1.21
1.2	39.22	25.49	17.83	13.14	10.07	7.95	6.43	5.3	4.43	3.58 3.76	2.84 3.23	2.28 2.8	1.85 2.44	1.52 2.15	1.26 1.9	1.05 1.7	0.88 1.52