

EP55

Caratteristiche statiche

Spessore	Peso Kg/m ²	Peso Kg/m	
		1000	1250
0.8	10.47	6.28	7.85
1.0	13.08	7.85	9.81
1.2	15.7	9.42	11.78
1.5	19.5	11.7	14.62



Trusca Profilati s.r.l.
STEEL SERVICE CENTRE

EP55 Soletta H=10 cm

Spessore	Sovraccarico di esercizio utile uniformemente distribuito in kN/m ²																
mm	1 campata																
	$\overline{\Lambda \Lambda}$	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	7.00	8.00	10.00	12.00	15.00	20.00
0.8	2.60	2.60	2.60	2.60	2.60	2.60	2.60	2.60	2.60	2.60	2.60	2.37	2.14	1.82	1.60	1.37	1.13
1.0	2.87	2.87	2.87	2.87	2.87	2.87	2.87	2.87	2.87	2.87	2.87	2.68	2.43	2.08	1.83	1.58	1.31
1.2	3.08	3.08	3.08	3.08	3.08	3.08	3.08	3.08	3.08	3.08	3.08	2.90	2.64	2.26	1.99	1.72	1.43
1.5	3.34	3.34	3.34	3.34	3.34	3.34	3.34	3.34	3.34	3.34	3.34	3.22	2.93	2.51	2.22	1.92	1.60

EP55 Soletta H=10 cm

Spessore	Sovraccarico di esercizio utile uniformemente distribuito in kN/m ²															
mm	2 campate															
	$\overline{\Lambda \Lambda \Lambda}$	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	7.00	8.00	10.00	12.00	15.00
0.8	3.25	3.25	3.24	3.01	2.83	2.65	2.50	2.37	2.26	2.16	2.00	1.87	1.67	1.53	1.37	1.09
1.0	3.72	3.62	3.35	3.06	2.83	2.65	2.50	2.37	2.26	2.16	2.00	1.87	1.67	1.53	1.37	1.14
1.2	4.02	3.74	3.35	3.06	2.83	2.65	2.50	2.37	2.26	2.16	2.00	1.87	1.67	1.53	1.37	1.14
1.5	4.21	3.74	3.35	3.06	2.83	2.65	2.50	2.37	2.26	2.16	2.00	1.87	1.67	1.53	1.37	1.18

EP55 Soletta H=10 cm

Spessore	Sovraccarico di esercizio utile uniformemente distribuito in kN/m ²															
mm	N campate															
	$\overline{\Lambda \Lambda \Lambda \Lambda}$	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	7.00	8.00	10.00	12.00	15.00
0.8	3.16	3.16	3.16	3.16	2.99	2.85	2.69	2.55	2.43	2.33	2.16	2.02	1.80	1.65	1.42	1.12
1.0	3.49	3.49	3.49	3.27	3.05	2.85	2.69	2.55	2.43	2.33	2.16	2.02	1.80	1.65	1.47	1.18
1.2	3.77	3.77	3.55	3.30	3.05	2.85	2.69	2.55	2.43	2.33	2.16	2.02	1.80	1.65	1.47	1.24
1.5	4.11	3.93	3.61	3.30	3.05	2.85	2.69	2.55	2.43	2.33	2.16	2.02	1.80	1.65	1.47	1.28