

## EP55

### Caratteristiche statiche

Spessore	Peso Kg/m <sup>2</sup>	Peso Kg/m	
		1000	1250
0.8	10.47	6.28	7.85
1.0	13.08	7.85	9.81
1.2	15.7	9.42	11.78
1.5	19.5	11.7	14.62



**Trusca Profilati** s.r.l.  
STEEL SERVICE CENTRE

## EP55 Soletta H=11 cm

Spessore	Sovraccarico di esercizio utile uniformemente distribuito in kN/m <sup>2</sup>															
mm	1 campata															
	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	7.00	8.00	10.00	12.00	15.00	20.00
0.8	2.49	2.49	2.49	2.49	2.49	2.49	2.49	2.49	2.49	2.49	2.49	2.30	1.95	1.71	1.46	1.20
1.0	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.62	2.23	1.97	1.69	1.40
1.2	2.96	2.96	2.96	2.96	2.96	2.96	2.96	2.96	2.96	2.96	2.96	2.83	2.42	2.14	1.84	1.53

## EP55 Soletta H=11 cm

Spessore	Sovraccarico di esercizio utile uniformemente distribuito in kN/m <sup>2</sup>															
mm	2 campate															
	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	7.00	8.00	10.00	12.00	15.00	20.00
0.8	3.06	3.06	3.06	3.06	2.92	2.74	2.58	2.45	2.33	2.23	2.07	1.93	1.73	1.58	1.41	1.20
1.0	3.56	3.56	3.46	3.16	2.92	2.74	2.58	2.45	2.33	2.23	2.07	1.93	1.73	1.58	1.41	1.22
1.2	3.86	3.86	3.46	3.16	2.92	2.74	2.58	2.45	2.33	2.23	2.07	1.93	1.73	1.58	1.41	1.22

## EP55 Soletta H=11 cm

Spessore	Sovraccarico di esercizio utile uniformemente distribuito in kN/m <sup>2</sup>															
mm	N campate															
	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	7.00	8.00	10.00	12.00	15.00	20.00
0.8	3.03	3.03	3.03	3.03	3.03	2.95	2.78	2.64	2.52	2.41	2.23	2.09	1.87	1.7	1.52	1.24
1.0	3.35	3.35	3.35	3.35	3.15	2.95	2.78	2.64	2.52	2.41	2.23	2.09	1.87	1.7	1.52	1.3
1.2	3.62	3.62	3.62	3.41	3.15	2.95	2.78	2.64	2.52	2.41	2.23	2.09	1.87	1.70	1.52	1.32