

EP75

Caratteristiche statiche

Spessore	Peso Kg/m ²	Peso Kg/m 1000
0.8	11.02	6.28
1.0	13.77	7.85
1.2	16.53	9.42



Trusca Profilati s.r.l.
STEEL SERVICE CENTRE

EP75 Soletta H=12 cm

Spessore	Sovraccarico di esercizio utile uniformemente distribuito in kN/m ²															
mm	Λ Λ		1 campata													
	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	7.00	8.00	10.00	12.00	15.00	20.00
0.8	3.35	3.35	3.35	3.35	3.35	3.15	2.86	2.65	2.48	2.33	2.09	1.91	1.65	1.46	1.27	1
1.0	3.65	3.65	3.65	3.65	3.65	3.35	3.08	2.86	2.68	2.53	2.28	2.08	1.8	1.6	1.35	1.01
1.2	3.89	3.89	3.89	3.89	3.89	3.55	3.27	3.04	2.85	2.69	2.43	2.22	1.93	1.69	1.35	1.01

EP75 Soletta H=12 cm

Spessore	Sovraccarico di esercizio utile uniformemente distribuito in kN/m ²															
mm	Λ Λ Λ			2 campate												
	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	7.00	8.00	10.00	12.00	15.00	20.00
0.8	3.82	3.82	3.56	3.32	3.08	2.88	2.71	2.5	2.37	2.17	1.86	1.63	1.3	1.09	0.87	0.65
1.0	4.45	4.06	3.64	3.32	3.08	2.88	2.71	2.57	2.45	2.28	2.07	1.81	1.45	1.21	0.97	0.72
1.2	4.7	4.07	3.64	3.32	3.08	2.88	2.71	2.57	2.45	2.35	2.11	1.89	1.51	1.26	1.01	0.76

EP75 Soletta H=12 cm

Spessore	Sovraccarico di esercizio utile uniformemente distribuito in kN/m ²															
mm	Λ Λ Λ Λ				N campate											
	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	7.00	8.00	10.00	12.00	15.00	20.00
0.8	4.02	4.02	3.82	3.58	3.32	3.1	2.84	2.68	2.44	2.24	1.92	1.68	1.34	1.12	0.89	0.67
1.0	4.41	4.24	3.93	3.58	3.32	3.1	2.93	2.78	2.57	2.46	2.13	1.86	1.49	1.24	0.99	0.75
1.2	4.79	4.39	3.93	3.58	3.32	3.1	2.93	2.78	2.65	2.46	2.22	1.94	1.55	1.3	1.04	0.78