

EP75

Caratteristiche statiche

Spessore	Peso Kg/m ²	Peso Kg/m 1000
0.8	11.02	6.28
1.0	13.77	7.85
1.2	16.53	9.42



Trusca Profilati s.r.l.
STEEL SERVICE CENTRE

EP75 Soletta H=14cm

Spessore	Sovraccarico di esercizio utile uniformemente distribuito in kN/m ²															
mm	1 campata															
	$\overline{\Lambda \quad \Lambda}$	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	7.00	8.00	10.00	12.00	15.00
0.8	3.07	3.07	3.07	3.07	3.07	3.07	3.07	2.95	2.76	2.59	2.33	2.12	1.87	1.62	1.4	1.15
1.0	3.35	3.49	3.49	3.49	3.49	3.49	3.35	3.32	3.1	2.92	2.62	2.39	2.06	1.83	1.58	1.26
1.2	3.58	3.58	3.58	3.58	3.58	3.58	3.58	3.53	3.3	3.11	2.8	2.56	2.21	1.97	1.7	1.28

EP75 Soletta H=14 cm

Spessore	Sovraccarico di esercizio utile uniformemente distribuito in kN/m ²															
mm	2 campate															
	$\overline{\Lambda \quad \Lambda \quad \Lambda}$	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	7.00	8.00	10.00	12.00	15.00
0.8	3.37	3.37	3.37	3.37	3.33	3.11	2.94	2.79	2.66	2.54	2.21	1.94	1.55	1.29	1.03	0.77
1.0	3.93	3.93	3.93	3.6	3.33	3.11	2.94	2.79	2.66	2.54	2.35	2.11	1.69	1.41	1.13	0.84
1.2	4.57	4.4	3.94	3.6	3.33	3.11	2.94	2.79	2.66	2.54	2.35	2.2	1.76	1.46	1.17	0.88

EP75 Soletta H=14 cm

Spessore	Sovraccarico di esercizio utile uniformemente distribuito in kN/m ²															
mm	N campate															
	$\overline{\Lambda \quad \Lambda \quad \Lambda \quad \Lambda}$	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	7.00	8.00	10.00	12.00	15.00
0.8	3.64	3.64	3.64	3.64	3.59	3.36	3.17	3	2.86	2.66	2.28	1.99	1.6	1.33	1.06	0.8
1.0	4.04	4.04	4.04	3.88	3.59	3.36	3.17	3	2.86	2.74	2.49	2.17	1.74	1.45	1.16	0.87
1.2	4.41	4.41	4.25	3.88	3.59	3.36	3.17	3	2.86	2.74	2.54	2.26	1.81	1.51	1.21	0.9